



DS-K1T341CMFW Face Recognition Terminal



Face recognition terminal adopts deep learning algorithm, which helps to recognize the face faster with higher accuracy. It also supports multiple authentication modes: face/card/fingerprint/PIN authentication, etc. It can be applied in multiple scenarios, such as buildings, enterprises, financial industries, and other important areas.

- Deep learning algorithm
- 4.3-inch capacitive touch screen, 2 MP wide-angle dual-lens
- 3,000 face capacity, 3,000 card capacity, 3,000 fingerprint capacity and 150,000 event capacity
- Multiple authentication modes, including face, fingerprint and card, etc.
- Face recognition duration < 0.2 s/User
- Supports mask wearing detection
- Connects to external access controller or Wiegand card reader via Wiegand protocol
- Connects to secure door control unit via RS-485 protocol to avoid the door opening when the terminal is destroyed
- Two-way audio with client software, door station, indoor station, and main station





Specification

Display				
Screen size	4.3 inch			
Operation method	Capacitive touch screen			
Туре	IPS			
Video				
Lens	2			
Resolution	2 MP (video stream: 720P)			
FOV	HFOV = 41.5°; VFOV = 75.5°; DFOV = 87°			
Audio				
Audio quality	Noise suppression and echo cancellation			
Network				
Wired network	Support			
Wi-Fi	Support, 2.4 G, 802.11b/g/n			
Interface				
Network interface	1 RJ-45, 10/100 M self-adaptive			
Lock control	1			
Exit button	1			
Door contact input	1			
TAMPER	1			
RS-485	1,RS-485 (Half duplex,HIKVISION)			
Wiegand	1,Wiegand (Hik 26bit,Hik 34bit)			
USB	1			
Authentication				
Card type	M1 card			
General				
Built-in access controller	Yes			
Power supply	12 VDC to 24 VDC, 2 A			
Power consumption	≤ 10 W			
Working temperature	-30 °C to 60 °C (-22 °F to 140 °F)			
Language English, Spanish (South America), Arabic, Thai, Indonesian, Russian, Vie Portuguese (Brazil), Korean				
Function	Totagaese (brazil), Noreali			
Hik-Connect	Support			
QR code recognition	Support			
Face anti-spoofing	Support			
Audio prompt	Support			
Audio prompt				






Available Model

DS-K1T341CMFW

Dimension







Accessory

Optional

DS-KAB6-D1 Base Bracket	DS-KAB6-ZU1 Brackets for face terminals	DS-KAB671-P2 Stand Stick	DS-KAB34X-S1 Protective Shield
7			